



DIMITECH

DTX2-4100C

Microkite

PIC32 Processing Module

DATA SHEET

TO OUR VALUED CUSTOMERS

It is a rule for us to try to provide our valued customers with the best documentation possible to ensure the successful implementation and use of our products. We will continue to improve our documentation to provide you with the maximum for your needs.

To obtain the most recent version of this data sheet, please visit our web site at <http://www.dimitech.com> or contact as at one of our publicly available email addresses.

You can determine the version of a data sheet by checking its version number found on the bottom left corner of the front page.

Every effort is made to verify the accuracy of information provided in this document, but no representation or warranty can be given and no liability assumed by Dimitech with respect to the accuracy and/or use of any products or information described in this document.

Any other products or information, subject to patents or innovations and mentioned in this data sheet are property to their lawful owners.

Dimitech will not be responsible for any patent infringements arising from the use of these products or information, and does not authorise or warrant the use of any of its products in life support devices without an explicit and official written permission.

Dimitech reserves the right to introduce changes to this document as well as the device(s) that it describes.

1. Overview

Feature Highlights


68-pin device in standard PLCC68 package; three possible ways of PCB mounting
DTX bus pin-compatible
Wide range input 4-20V DC power supply with capability of provision to external circuit
Fully self-contained – does not need any external components to run
32-bit architecture
Extended clone of the popular Micromite MMBasic® available for easy development¹
Up to 33 I/O lines
microSD card connector on board
Three built-in LEDs, one of which accessible by software
Tag-Connect® pads on board for easy firmware programming
RoHS compliant

Typical Applications

- Hobby and academic projects
- Robotics and various toys
- Automotive and industrial automation devices
- Portable electronics
- Data logging

1. *planned functionality*

2. Pinout



Pinout Summary

Pin	Name	Type	Description
1			No connection
2			No connection
3			No connection
4			No connection
5	TX	O	Console "data transmit" line
6	RX	I	Console "data receive" line
7	GND	P	Ground

8	+VBAT	P	Positive power lead
9	PWRON	I	Power enabling input (can be connected directly to +VBAT); active high
10	+VBAT	P	Positive power lead
11	GND	P	Ground
12	+3V3OUT	P	+3.3V output from the internal regulator; can be used to supply power to external components and circuits
13	\sim RESET	I,5V	$\overline{\text{RESET}}$ line; internally biased to +3.3V
14	P30/PGD	I,O,5V	MCU programming data line (shared with P30)
15	P31/PGC	I,5V	MCU programming clock line (shared with P31)
16			No connection
17	VBUS	I,5V	I/O port or USB Vbus power detection input
18	D-	I,O	I/O port or USB D- line
19	D+	I,O	I/O port or USB D+ line
20			No connection
21			No connection
22			No connection
23			No connection
24			No connection
25			No connection
26	P32/ \sim uSD	I,O,OD	General purpose I/O port (shared with microSD card selection line)
27			No connection
28	GND	P	Ground
29	P31/PGC	I,O,OD,5V	General purpose I/O port (shared with MCU programming clock)
30	P30/PGD	I,O,OD,5V	General purpose I/O port (shared with MCU programming data)
31	P29	I,O,OD,5V	General purpose I/O port
32	P28	A,I,O,OD	General purpose I/O port
33	P27	A,I,O,OD	General purpose I/O port
34	P26	A,I,O,OD	General purpose I/O port
35	P25	A,I,O,OD	General purpose I/O port
36	P24	A,I,O,OD	General purpose I/O port (PWM2B)
37	P23	A,I,O,OD	General purpose I/O port (PWM2A)
38	P22	A,I,O,OD	General purpose I/O port

			<i>(PWM1C)</i>
39	P21	A,I,O,OD	General purpose I/O port <i>(PWM1B)</i>
40	P20	A,I,O,OD	General purpose I/O port <i>(PWM2B)</i>
41	P19	I,O,OD	General purpose I/O port <i>(TX2)</i>
42	P18	I,O,OD	General purpose I/O port <i>(RX2)</i>
43	P17	I,O,OD,5V	General purpose I/O port <i>(counter input)</i>
44	P16	A,I,O,OD	General purpose I/O port <i>(RS485 data enable output)</i>
45	P15	I,O,OD,5V	General purpose I/O port <i>(TX1 or interrupt input)</i>
46	P14	I,O,OD,5V	General purpose I/O port <i>(RX1 or interrupt input)</i>
47	P13	I,O,OD,5V	General purpose I/O port <i>(IR data or interrupt input)</i> <i>(wakeup from sleep input)</i> <i>(built-in pull-up resistor)</i>
48	P12	I,O,OD,5V	General purpose I/O port <i>(I²C SCL or counter input)</i> <i>(built-in pull-up resistor)</i>
49	P11	I,O,OD,5V	General purpose I/O port <i>(I²C SDA or counter input or interrupt input)</i> <i>(built-in pull-up resistor)</i>
50	P10	I,O,OD,5V	General purpose I/O port <i>(built-in pull-up resistor)</i>
51	P9	I,O,OD,5V	General purpose I/O port
52	P8	I,O,OD,5V	General purpose I/O port
53	P7	A,I,O,OD	General purpose I/O port <i>(interrupt input)</i>
54	P6	A,I,O,OD,5V	General purpose I/O port <i>(interrupt input)</i>
55	P5	A,I,O,OD,5V	General purpose I/O port <i>(interrupt input)</i>
56	P4	A,I,O,OD,5V	General purpose I/O port <i>(interrupt input)</i>
57	P3/~mSS	A,I,O,OD,5V	General purpose I/O port <i>(SPI/mSPI ~SS line)</i> <i>(interrupt input)</i>
58	P2/mSCK	A,I,O,OD	General purpose I/O port <i>(SPI/mSPI SCK line)</i> <i>(interrupt input)</i>

59	P1/MOSI	A,I,O,OD	General purpose I/O port (SPI/mSPI MOSI line) (interrupt input)
60	P0/MISO	I,O,OD,5V	General purpose I/O port (SPI/mSPI MISO line) (interrupt input)
61			No connection
62			No connection
63			No connection
64			No connection
65			No connection
66			No connection
67			No connection
68			No connection

Legend:

I – input with CMOS level

A – analogue input

O – digital output

P – power pin

5V – 5 volt tolerant pin

OD – open drain output

3. Electrical Parameters


ABSOLUTE MAXIMUM RATINGS:

Stresses beyond those listed under "absolute maximum ratings" may cause permanent damage to the device. These are stress ratings only, and functional operation of the device at these or any other conditions beyond those indicated under "recommended operating conditions" is not implied. Exposure to absolute-maximum-rated conditions for extended periods may affect device reliability.

parameter	min	typ	max	units
Power supply voltage range, pin +VBAT with respect to pin GND	3.5	9	20	V
Safe load on +3V3OUT pin			300	mA
Parameters of all other functional pins	According to function and IC manufacturer's recommendation			
Operating free-air temperature range	-20		+85	°C
Storage temperature range	-40		+90	°C

4. Mechanical Parameters

Note: All dimensions are given in millimetres



Dimitech Pty Ltd provides CAD schematic symbols and PCB footprints for the DTX series modules. For more information please visit our website: <http://www.dimitech.com/>.